

1. IDENTIFICATION

Product Identifier

Product Name OD-3003
ONDEK VINYL DECKING ADHESIVE - ALL SEASON

Other means of identification

Product Code(s) AM-0295
UN-No UN 1133
Product Type Adhesive

Recommended use of the chemical and restrictions on use

Recommended Use For industrial use only.
Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Address

Dural
550 Marshall Ave.
Dorval, PQ
Canada
H9P 1C9

Company Phone Number

800-361-2340

Emergency telephone number

Emergency Telephone Number CANUTEC 613-996-6666

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable liquids	Category 2

Label elements

Emergency Overview

Signal Word Danger

Hazard Statements

CAUSES SKIN IRRITATION
Causes serious eye irritation
May cause an allergic skin reaction
Suspected of damaging fertility or the unborn child
May be harmful if swallowed and enters airways

Flammable liquid and vapor



Appearance Colorless

Physical State Liquid

Odor Ketones

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Wear protective gloves/protective clothing/eye protection/face protection
Wash face, hands and any exposed skin thoroughly after handling
Contaminated work clothing must not be allowed out of the workplace
Do not breathe dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
Specific treatment (see Section 4 on this SDS)
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention
IF ON SKIN: Wash with plenty of water and soap
Take off contaminated clothing and wash it before reuse
If skin irritation or rash occurs: Get medical advice/attention
IF INHALED: Remove person to fresh air and keep comfortable for breathing
IF SWALLOWED: Immediately call a POISON CENTER or doctor
Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed
Keep from freezing

Precautionary Statements - Disposal

Dispose of in accordance with federal, state and local regulations

Hazards not otherwise classified (HNOC)

STATIC ACCUMULATING FLAMMABLE LIQUID CAN BECOME ELECTROSTATICALLY CHARGED EVEN IN BONDED AND GROUNDED EQUIPMENT
Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity)
Vapors may cause flash fire or explosion

Other Information

Unknown acute toxicity 4.54842 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Components	CAS No.	Weight-%	Trade Secret
Acetone	67-64-1	30-60	*
Hexane	110-54-3	15-30	*
Toluene	108-88-3	15-30	*
3-Methylpentane	96-14-0	5.0-15	*
2-Methylpentane	107-83-5	1-5%	*
Rosin	8050-09-7	<1.0%	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

Eye Contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. If symptoms persist, call a physician.
Skin Contact	Wash off immediately with soap and plenty of water. Take off contaminated clothing and wash before reuse. In the case of skin irritation or allergic reactions see a physician.
Inhalation	Move to fresh air in case of accidental inhalation of vapors. If symptoms persist, call a physician.
Ingestion	Immediate medical attention is required. Call a physician or Poison Control Center immediately. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Aspiration hazard if swallowed - can enter lungs and cause damage. Aspiration into lungs can produce severe lung damage. Observe risk of aspiration if vomiting occurs. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.
Notes to Physician	May cause sensitization by inhalation and skin contact. Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed. Potential for aspiration if swallowed. Observe risk of aspiration if vomiting occurs.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Alcohol-resistant foam, Water spray or fog

Small Fires

Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable Extinguishing Media

Do not use a solid water stream as it may scatter and spread fire.

Specific Hazards Arising from the Chemical

Do not allow run-off from fire-fighting to enter drains or water courses. Sealed containers may rupture when heated. Combustible material. Keep product and empty container away from heat and sources of ignition. Vapors may form explosive mixtures with air. May be ignited by heat, sparks or flames.

Explosion Data

Sensitivity to mechanical impact None.

Sensitivity to static discharge May be ignited by heat, sparks or flames. This liquid may accumulate static electricity when filling properly grounded containers. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Use personal protection equipment. Ensure adequate ventilation. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations. Keep people away from and upwind of spill/leak. Take precautionary measures against static discharges. Remove all sources of ignition.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Cleaning Up Pick up and transfer to properly labeled containers. Prevent environmental discharge consistent with regulatory requirements. Disposal should be in accordance with applicable regional, national and local laws and regulations. Take precautionary measures against

static discharges. Dike to collect large liquid spills. Take up with inert, damp, noncombustible material using clean non-sparking tools and place into loosely plastic containers for later disposal. Following product recovery, flush area with water.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with eyes, skin and clothing. Keep away from open flames, hot surfaces and sources of ignition. Do not breathe vapor or mist. In case of insufficient ventilation, wear suitable respiratory equipment.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a cool, well-ventilated place. Keep from freezing.

Incompatible Products Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Components	ACGIH TLV	OSHA PEL	NIOSH IDLH	AIHA - WEEL
Acetone 67-64-1	BEI: 25 mg/L urine 500 ppm STEL TWA: 250 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m ³	-
Hexane 110-54-3	BEI: 0.4 mg/L urine TWA: 50 ppm Skin	TWA: 500 ppm TWA: 1800 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 180 mg/m ³ (vacated) TWA: 500 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 1000 ppm (vacated) STEL: 3600 mg/m ³	IDLH: 1100 ppm TWA: 50 ppm TWA: 180 mg/m ³	-
Toluene 108-88-3	BEI: 0.02 mg/L blood BEI: 0.03 mg/L urine BEI: 0.3 mg/g creatinine urine TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³	-
3-Methylpentane 96-14-0	1000 ppm STEL (listed under Hexane isomers other than n-hexane) 1000 ppm STEL TWA: 500 ppm	(vacated) TWA: 500 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 1000 ppm (vacated) STEL: 3600 mg/m ³	Ceiling: 510 ppm Ceiling: 1800 mg/m ³ TWA: 100 ppm TWA: 350 mg/m ³	-
2-Methylpentane 107-83-5	1000 ppm STEL (listed under Hexane isomers other than n-hexane) 1000 ppm STEL TWA: 500 ppm	(vacated) TWA: 500 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 1000 ppm (vacated) STEL: 3600 mg/m ³	Ceiling: 510 ppm Ceiling: 1800 mg/m ³ TWA: 100 ppm TWA: 350 mg/m ³	-
Rosin 8050-09-7	-	(vacated) TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³	-

Appropriate engineering controls

Engineering Measures Ensure adequate ventilation, especially in confined areas. Showers. Eyewash stations.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Avoid contact with eyes. Face-shield. Safety glasses with side-shields.

Skin and Body Protection Wear protective gloves/protective clothing.

Respiratory Protection Use only with adequate ventilation. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved organic vapour respiratory protection should be worn.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Take off contaminated clothing and wash before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Liquid	Odor	Ketones
Appearance	Colorless	Odor Threshold	No data available
Color	Clear; Natural		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	Not Applicable	
Melting point / freezing point	No information available	
Boiling Point / Boiling Range	Specific test data for the substance or mixture is not available	
Flash Point	-18 °C	
Evaporation Rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper Explosive Limits	Specific test data for the substance or mixture is not available	
Lower Explosive Limits	Specific test data for the substance or mixture is not available	
Vapor pressure	Negligible	
Vapor Density	Specific test data for the substance or mixture is not available	
Specific Gravity	0.80	
Water Solubility	Slightly soluble	
Solubility in other solvents	Specific test data for the substance or mixture is not available	
Partition coefficient	No information available	
Autoignition Temperature	223 °C	
Decomposition Temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	180-220 cps	
Explosive Properties	No information available	
Oxidizing Properties	No information available	

Other Information

Softening Point	Specific test data for the substance or mixture is not available
Solids	18 %

10. STABILITY AND REACTIVITY

Reactivity

None under normal processing
None under normal processing

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to Avoid

Keep away from open flames, hot surfaces and sources of ignition.

Incompatible Materials

Strong oxidizing agents

Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating gases and vapors. Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation May cause irritation of respiratory tract. Avoid breathing vapors or mists. Symptoms of overexposure are dizziness, headache, tiredness, nausea, unconsciousness, cessation of breathing. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.

Eye Contact Severely irritating to eyes.

Skin Contact Repeated exposure may cause skin dryness or cracking. Prolonged skin contact may defat the skin and produce dermatitis. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.

Ingestion Not an expected route of exposure. May be harmful if swallowed.

Components	Oral LD50	Dermal LD50	Inhalation LC50
Acetone 67-64-1	= 5800 mg/kg (Rat)	-	= 50100 mg/m ³ (Rat) 8 h
Hexane 110-54-3	= 25 g/kg (Rat) = 15000 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	= 48000 ppm (Rat) 4 h
Toluene 108-88-3	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h
3-Methylpentane 96-14-0	= 15000 mg/kg (Rat)	-	-
2-Methylpentane 107-83-5	= 15000 mg/kg (Rat)	-	-
Rosin 8050-09-7	= 7600 mg/kg (Rat)	> 2500 mg/kg (Rabbit)	= 1.5 mg/L (Rat) 4 h

Information on toxicological effects

Symptoms Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization May cause sensitization in susceptible persons.
Mutagenic Effects Specific test data for the substance or mixture is not available.
Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Components	ACGIH	IARC	NTP	OSHA
Toluene 108-88-3	-	Group 3	-	-

Reproductive Toxicity No information available
STOT - single exposure No information available.
STOT - repeated exposure No information available.
Neurological Effects Repeated or prolonged overexposure to solvents may cause permanent damage to the nervous system.
Aspiration Hazard Risk of serious damage to the lungs (by aspiration).

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 7,525.00
ATEmix (dermal) 14,377.00

12. ECOLOGICAL INFORMATION

Ecotoxicity

7.29911768 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Components	Algae/aquatic plants	Toxicity to Fish	Daphnia Magna (Water Flea)
Acetone - 67-64-1	N/A	4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L LC50 6210 - 8120: 96 h Pimephales promelas mg/L LC50 static 8300: 96 h Lepomis macrochirus mg/L LC50	10294 - 17704: 48 h Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h Daphnia magna mg/L EC50
Hexane - 110-54-3	N/A	2.1 - 2.98: 96 h Pimephales promelas mg/L LC50 flow-through	N/A
Toluene - 108-88-3	433: 96 h Pseudokirchneriella	15.22 - 19.05: 96 h Pimephales	11.5: 48 h Daphnia magna mg/L

	subcapitata mg/L EC50 12.5: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	promelas mg/L LC50 flow-through 12.6: 96 h Pimephales promelas mg/L LC50 static 5.89 - 7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static 5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50 static 54: 96 h Oryzias latipes mg/L LC50 static 28.2: 96 h Poecilia reticulata mg/L LC50 semi-static 50.87 - 70.34: 96 h Poecilia reticulata mg/L LC50 static	EC50 5.46 - 9.83: 48 h Daphnia magna mg/L EC50 Static
Rosin - 8050-09-7	400: 72 h Desmodemus subspicatus mg/L EC50	N/A	3.8 - 5.4: 48 h Daphnia magna mg/L EC50

Persistence and Degradability

No information available.

Bioaccumulation/Accumulation

No information available.

Components	log Pow
Acetone 67-64-1	-0.24
Toluene 108-88-3	2.65

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal Methods

Dispose of in accordance with federal, state and local regulations. This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated Packaging

Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Dispose of in accordance with local regulations.

14. TRANSPORT INFORMATION

DOT

UN-No
Proper Shipping Name
Hazard Class
Packing Group
Transport Label

Regulated
UN 1133
Adhesives, (Acetone, Hexane, Toluene)
3
II



IATA

Regulated

IMDG/IMO

Regulated

15. REGULATORY INFORMATION

TSCA 8(b) All components are listed or exempt
DSL All components are listed or exempt

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Components	Weight-%	SARA 313 - Threshold Values %
Hexane - 110-54-3	16.8025	1.0
Toluene - 108-88-3	16.2561	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:

Components	Weight-%	HAPS data
Hexane 110-54-3	15-30	Present
Toluene 108-88-3	15-30	Present
2-Chloro-1,3-butadiene 126-99-8	<0.1%	Present
Formaldehyde 50-00-0	<0.1%	Present

CWA (Clean Water Act)

See information supplied by the manufacturer

CERCLA

See information supplied by the manufacturer

US State Regulations

California Proposition 65

This product contains (a) Proposition 65 chemical(s)

U.S. EPA Label Information

EPA Pesticide Registration Number No data available

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Health Hazard 1	Flammability 3	Instability 0	Physical and Chemical Hazards -
HMIS / WHMIS	Health Hazard 1	Flammability 3	Physical hazards 0	Personal Precautions X

Revision Date

Revision Note

No information available

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet